

RIKON

POWER TOOLS

DRILL PRESS SERIES



DRILL PRESS SERIES

The RIKON Drill Press Series contains 4 bench (8"-15") and 4 floor (13"-20") models. Each features solid cast-iron handles, locking depth stop with gauge, toggle switch, induction motor and a speed selection chart. 10"-20" all have rack & pinion table height adjustments. They are built with a rugged cast iron base, head and tilting table. The powerful, efficient, and smooth operation is ideal for the hobbyist and professional.

**THE RIKON
ADVANTAGE**



Model:	30-100	30-110	30-120	30-200	30-130	30-210	30-230	30-240
Swing	8"	10"	13"	13"	15"	15"	17"	20"
Type	Bench	Bench	Bench	Floor	Bench	Floor	Floor	Floor
Motor	1/4-HP	1/3-HP	1/2-HP	1/2-HP	1/2-HP	1/2-HP	3/4-HP	1-HP
Chuck Size	1/2"	1/2"	5/8"	5/8"	5/8"	5/8"	3/4"	3/4"
Drilling Capacity	1/2"	1/2"	5/8"	5/8"	3/4"	3/4"	1"	1"
Spindle Travel	2"	2-3/8"	3-1/8"	3-1/8"	3-1/8"	3-1/8"	3-1/8"	4-3/4"
Spindle Taper	JT33	JT33	MT2	MT2	MT2	MT2	MT3	MT3
Speeds	5	5	16	16	16	16	16	12
Speed Range	620-3,100	620-3,100	220-3,600	220-3,600	220-3,600	220-3,600	200-3,630	150-4,200
Quill Diameter	1-1/2"	2-3/16"	2-3/16"	2-3/16"	2-3/8"	2-3/8"	3"	3"
Table	6-1/2" x 6-1/2"	7-3/4" x 7-3/4"	11-13/16" Round	11-13/16" Round	11-3/8" x 11-3/8"	11-3/8" x 11-3/8"	14" x 14"	16-1/2" x 18-3/4"
Table Tilts	45°	45°	45°	45°	45°	45°	45°	45°
Table Rotates	N/A	N/A	360°	360°	360°	360°	360°	360°
Column Diam.	2"	2"	2-3/8"	2-7/8"	3-3/16"	3-3/16"	3-3/16"	3-5/8"
Overall Height	23"	28-1/2"	39"	64"	42"	64-3/8"	64-3/8"	68"
Weight	42 lbs	59 lbs	121 lbs	128 lbs	135 lbs	148 lbs	188 lbs	318 lbs
Light	No	No	No	No	Yes	Yes	Yes	Yes
Chuck Key Holder	No	Yes	Yes	Yes	Yes	Yes	Yes	Yes

WWW.RIKONTOOLS.COM

FEATURES



Convenient Chuck Key Holder



Speed Selection Chart



Solid Cast Iron Handles



Toggle Safety Switch



Clutch Depth Stop



Table Rotates 360° Tilting Table



Rugged Cast-Iron Base


Optional Accessories



Safety Guard



Mortising Attachment w/ 4 Chisels



2-1/2" - 6" Drill Press Vises

RIKON
POWER TOOLS

WWW.RIKONTOOLS.COM



Part # 30-100SS2