

The Wayback Machine - <https://web.archive.org/web/20010124070000/http://www.taunton.com:80/fw/features/tools/62reid.htm>

[HOME](#)



[CURRENT ISSUE](#)

The Magazine

- [Subscribe](#)
- [Current Issue](#)
- [Back Issues](#)
- [Magazine Index](#)
- [About Us](#)
- [About Your Safety](#)

Articles & Tips

- [Tools](#)
- [Techniques](#)
- [Materials](#)
- [Projects](#)

Online Extras

- [Discussion:](#)
- [Knots](#)
- [Classifieds](#)
- [Sites to See](#)
- [Events](#)
- [Meetings](#)
- [Schools](#)
- [Clubs](#)

Books & Videos

- [Books](#)
- [Videos](#)
- [TauntonPLUS](#)

Help

- [Customer Service](#)
- [Email Us](#)
- [Help - FAQ's](#)
- [Search](#)



Micro-Adjustable Router Fence: parts list

A parts list for readers who want to build the fence described in Pat Warner's "Micro-Adjustable Router Fence" in the September/October issue of *Fine Woodworking* magazine. The list is organized by supplier and includes part numbers.

From Reid Tool Supply (800-253-0421):

- Bronze bearing (5/16 in. ID x 3/8 in. OD x 3/4 in. length)
OIB-115
- 2 screws to hold aluminum in movable adjustment block (1/4-20 x 1 in.)
FCS-64
- 2 screws to affix movable block to carrier (5/16-18 x 1-1/2 in.)
FCS-84
- 2 screws to hold fixed block on base (5/16-18 x 1-1/2 in.)
FCS-84
- 2 screws to attach dial indicator holder to base (1/4-20 x 1-1/4 in.)
FCS-66
- 1 buttonhead screw to hold dial indicator (1/4-20 x 1 in.)
BHC-4050
- 2 screws to attach aluminum guides to base (1/4-20 x 3/8 in.)
FCS-62

2 nylon washers for knob assembly
CT-533

1 flange nut for knob assembly (5/16- 18)
FNC-2

1 lock nut (5/16-18)
MHN-3320

6 in. of 5/16-18 all-thread
AMS-222 (or hardware store)

4 bolts to hold fence halves down (5/16-18 x 2-1/4)
FCS-90

1 flat foot stop and screw for dial indicator
JFF-19304

2 levers to clamp carrier to base (1/4-20)
KHB-255

2 flat feet washers for above levers
JFF-19304

1 dial indicator
SO-200-720

1 buttonhead cap screw to attach rule (8-32 x 5/8 in.)
BHC-4022

2 levers to clamp fence base to router table
KHB-16

2 flat feet washers for above levers
JFF-19305

2 studs for above levers (5/16-18 x 3 in.)
AMS-217

Eight screws for fence faces to ash beams (1/4-20X1-1/2)
FCS-68

1 knob for spindle assembly
JCL-705

From Bruss Fasteners (800-536-0009):

4 Propell Nuts (T-nuts) for the larger clamp levers (5/16-18)

2 Propell Nuts (T-nuts) for smaller clamp levers (1/4-20)

From DeWalt (800-433-9258):

DeWalt plastic vacuum fitting (1-1/2 in.)
328592-00

From L.S. Starrett (978-249-3551):

3-in. Starrett rule
C604R-3

Aluminum sources

www.metalmart.com (800-657-0721)

www.asapsource.com (734-213-ASAP)

www.use-enco.com (800-873-3626)

Aluminum bars for guides and movable adjustment block
(20 in. of 1/4-in. by 1 in. stock, 6061 is a good standard grade)

Aluminum for long washers
(21 in. of 3/8 in. by 1-1/4 in. stock, 6061 grade)

--An online extra. If you encounter difficulty building this jig, you can email Pat Warner for advice at pat@patwarner.com. For the complete article, see FW #144.

Also See:

More from finewoodworking.com :

- Don't miss the rest of our features in [Tools](#)
- Take a peek at this month's [Fine Woodworking Current Issue](#)
- It's fast, it's safe, it's risk-free! [Subscribe to Fine Woodworking](#)
- Complete your collection with our mint-condition [Back Issues](#)
- Join the discussion at [Knots](#)

[TOOLS](#) | [TECHNIQUES](#) | [MATERIALS](#) | [PROJECTS](#)

[Fine Woodworking Home](#) | [Search FineWoodworking.com](#)

More from The Taunton Press:

Š by The Taunton Press, Inc. Used by permission. Read our [Privacy Policy](#).